

# REC Batteries

- VRLA batteries designed for cycle discharge. Long –life term , non-spillable, small size, maintenance free. Apply to electric vehicle, electric bikes.



## + Specifications

## Assembly Fig

## Features

(Model)	Nominal Voltage (V)	Capacity(AH)			Nominal Wattage		Dimensions (mm)			Weight Approx. (kg)	Terminal	Terminal Layout	Flame class	Life Expectancy
		5 HR	10 HR	20 HR	10min rate	15min rate	(L)	(W)	Overall (H)					
<u>REC10-12</u>	12	-	-	10.0	-	-	151	65	115.5	3.4	B	4	UL94HB	-
<u>REC12-12</u>	12	-	-	12.0	-	-	151	98	97.5	4.2	B	4	UL94HB	-
<u>REC14-12</u>	12	-	-	13.0	-	-	151	98	97.5	4.2	B	4	UL94HB	-
<u>REC22-12</u>	12	-	-	22.0	-	-	181	76.2	167	6.4	C	2	UL94HB	-
<u>REC50-12</u>	12	-	-	45.0	-	-	197	165	175.0	15.7	G	2	UL94HB	-
<u>REC80-12</u>	12	-	-	80.0	-	-	259	168	212.5	27.0	G	1	UL94HB	-
<u>U1-36E-12</u>	12	-	-	36.0	-	-	196	130	169	11.2	I	1	UL94HB	-

## Discharge Characteristic Curves : Standard Batteries

